

WIELAND

Wieland Wood Finish Care

WOOD FINISH SYSTEM

Wieland's 2K Polyurethane wood finishing system is applied with the latest in computer controlled equipment. This 2-component or 2K, polyurethane sealer and top coat has all the advantages of traditional catalyzed varnish with the added benefits of increased durability and performance.

To test this Wieland created a test environment where each of the following noted chemicals were applied and rubbed dry 36,400 times. Each chemical was diluted to the manufactures recommendation: Bleach/Clorox, Isopropyl Alcohol/Equate, Peroxide/Oxycide, Quaternary Ammonium/Virex II 256, and Phenolic/Wexcide128.

After this very rigorous testing, the samples did not show a noticeable difference (Gloss Level, Film Thickness and Cross Hatch Adhesion) from the sample prior to testing. This is a real testament to the superior hard use resistance inherent with this finish chemistry.

CLEANING

- Everyday cleaning should be done with mild detergent or soap and warm water. Dry surfaces immediately with a soft cloth.
- Periodically apply a quality furniture polish to enhance the appearance and durability of the finish. Do not use products containing Silicone or Wax as they will make any future touch up virtually impossible.
- Do not use abrasive pads or powdered cleaners on the finished wood. Liquid polishes and cleaning solutions should be applied with a soft cloth or pre-saturated wipe.
- Following application of Sanitizing or Germicidal cleaning products, wipe the wood surface with a water-dampened cloth to remove any remaining residue that may damage the finish.

REPAIRS

- If a scratch or blemish has not penetrated the finish, it can often be hidden by applying a furniture polish containing a scratch concealing stain. If the scratch still shows after application, remove the polish by wiping with mineral spirits and apply a touch up stick in matching color. Fill in the scratch and rub to remove excess. Follow with polish and buff.